

APPENDIX 3.5-A: PRECONSTRUCTION ELECTROMAGNETIC MEASUREMENT SURVEY ALONG THE SAN JOSE TO MERCED PROJECT SECTION

California High-Speed Rail Authority

San Jose to Merced Project Section Draft Project EIR/EIS



CONTENTS

APPENDIX 3.5-A: PRECONSTRUCTION ELECTROMAGNETIC	
MEASUREMENT SURVEY ALONG THE SAN JOSE TO MERCED	
PROJECT SECTION	1
Introduction	4
Test Procedures and Equipment	5
Overview of the Measurement Results	
Magnetic Fields	5
Electric Fields	6
Individual Site Observations	9
Site 1 (Newhall Street / Newhall Drive)	9
Site 2 (Montgomery Street / Otterson Street)	9
Site 3 (Communications Hill Boulevard / Curtner Avenue)	10
Site 4 (Great Oaks Parkway / Las Colinas Road)	10
Site 5 (Metcalf Road / Coyote Ranch Road)	10
Site 6 (Railroad Avenue / Barrett Avenue)	10
Site 7 (Monterey Highway / Las Animas Ávenue)	10
Site 8 (State Route 152 / Casa de Fruta Parkway)	10
Site 9 (Santa Nella Avenue / Fahey Road)	10
Site 10 (Henry Miller Road / Carlucci Road)	10
Site Photographs and Measurement Data	10

Figures

Figure 1 Average Measured AC Magnetic Field Strengths	6
Figure 2 Maximum Electric Field Strengths by Frequency Band	7
Figure 3 Variation in Measured Maximum Electric Field Strengths	8
Figure 4 Maximum Measured Electric Field Strengths	9
Figure 5(a) Location 1: Newhall Street / Newhall Drive, San Jose	11
Figure 5(b) Location 1: Measurement Location and Site Views	12
Figure 5(c) Location 1: Local EMF Sources	13
Figure 5(d) Location 1: AC and DC Magnetic Field Measurement Results	14
Figure 5(e) Location 1: Measured Environmental RF Levels	15
Figure 5(f) Location 1: Measured Environmental RF Levels	16
Figure 5(g) Location 1: Measured Environmental RF Levels	17
Figure 5(h) Location 1: Measured Environmental RF Levels	18
Figure 6(a) Location 2: Montgomery Street / Otterson Street, San Jose	19
Figure 6(b) Location 2: Measurement Location and Site Views	20
Figure 6(c) Location 2: Local EMF Sources	21
Figure 6(d) Location 2: AC and DC Magnetic Field Measurement Results	22
Figure 6(e) Location 2: Measured Environmental RF Levels	23
Figure 6(f) Location 2: Measured Environmental RF Levels	24
Figure 6(g) Location 2: Measured Environmental RF Levels	25
Figure 6(h) Location 2: Measured Environmental RF Levels	26



Figure 7(a) Location 3: Communications Hill Boulevard/Monte Vista Drive, San Jose	. 27
Figure 7(b) Location 3: Measurement Location and Site Views	
Figure 7(c) Location 3: Local EMF Sources	
Figure 7(d) Location 3: Measured DC and AC Magnetic Field Strengths	
Figure 7(e) Location 3: Measured Environmental RF Levels Non-Directional Data from Vertically Oriented Monopole Antenna, Bands 0-4	
Figure 7(f) Location 3: Measured Environmental RF Levels Band 5 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation	
Figure 7(g) Location 3: Measured Environmental RF Levels Band 6 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation	
Figure 7(h) Location 3: Measured Environmental RF Levels Band 7 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation	
Figure 8(a) Location 4: Great Oaks Parkway/Las Colinas Road, San Jose	. 35
Figure 8(b) Location 4: Measurement Location and Site Views	. 36
Figure 8(c) Location 4: Local EMF Sources	. 37
Figure 8(d) Location 4: AC and DC Magnetic Field Measurement Results	
Figure 8(e) Location 4: Measured Environmental RF Levels Non-Directional Data from Vertically Oriented Monopole Antenna, Bands 0-4	. 39
Figure 8(f) Location 4: Measured Environmental RF Levels	
Figure 8(g) Location 4: Measured Environmental RF Levels	. 41
Figure 8(h) Location 4: Measured Environmental RF Levels	
Figure 9(a) Location 5: Metcalf Energy Center, San Jose	
Figure 9(b) Location 5: Measurement Location and Site Views	. 44
Figure 9(c) Location 5: Local EMF Sources	. 45
Figure 9(d) Location 5: AC and DC Magnetic Field Measurement Results	. 46
Figure 9(e) Location 5: Measured Environmental RF Levels	. 47
Figure 9(f) Location 5: Measured Environmental RF Levels	. 48
Figure 9(g) Location 5: Measured Environmental RF Levels	. 49
Figure 9(h) Location 5: Measured Environmental RF Levels	. 50
Figure 10(a) Location 6: Railroad Avenue/Barrett Avenue, Morgan Hill	. 51
Figure 10(b) Location 6: Measurement Location and Site Views	. 52
Figure 10(c) Location 6: Local EMF Sources	. 53
Figure 10(d) Location 6: AC and DC Magnetic Field Measurement Results	. 54
Figure 10(e) Location 6: Measured Environmental RF Levels	. 55
Figure 10(f) Location 6: Measured Environmental RF Levels	. 56
Figure 10(g) Location 6: Measured Environmental RF Levels	. 57
Figure 10(h) Location 6: Measured Environmental RF Levels	. 58
Figure 11(a) Location 7: Monterey Highway/Las Animas Avenue, Gilroy	. 59
Figure 11(b) Location 7: Measurement Location and Site Views	. 60
Figure 11(c) Location 7: Local EMF Sources	. 61
Figure 11(d) Location 7: AC and DC Magnetic Field Measurement Results	. 62



Figure 11(e) Location 7: Measured Environmental RF Levels	63
Figure 11(f) Location 7: Measured Environmental RF Levels	64
Figure 11(g) Location 7: Measured Environmental RF Levels	65
Figure 11(h) Location 7: Measured Environmental RF Levels	66
Figure 12(a) Location 8: SR 152/Casa de Fruta Parkway, Hollister	67
Figure 12(b) Location 8: Measurement Location and Site Views	68
Figure 12(c) Location 8: AC and DC Magnetic Field Measurement Results	69
Figure 12(d) Location 8: Measured Environmental RF Levels	70
Figure 12(e) Location 8: Measured Environmental RF Levels	
Figure 12(f) Location 8: Measured Environmental RF Levels	
Figure 12(h) Location 8: Measured Environmental RF Levels	73
Figure 13(a) Location 9: Santa Nella Avenue/Fahey Road, Santa Nella	74
Figure 13(b) Location 9: Measurement Location and Site Views	75
Figure 13(c) Location 9: Local EMF Sources	76
Figure 13(d) Location 9: AC and DC Magnetic Field Measurement Results	77
Figure 13(e) Location 9: Measured Environmental RF Levels	78
Figure 13(f) Location 9: Measured Environmental RF Levels	79
Figure 13(g) Location 9: Measured Environmental RF Levels	80
Figure 13(h) Location 9: Measured Environmental RF Levels	81
Figure 14(a) Location 10: Henry Miller Road/Carlucci Road, Dos Palos	82
Figure 14(b) Location 10: Measurement Location and Site Views	83
Figure 14(c) Location 10: Local EMF sources	84
Figure 14(d) Location 10: AC and DC Magnetic Field Measurement Results	85
Figure 14(e) Location 10: Measured Environmental RF Levels	
Figure 14(f) Location 10: Measured Environmental RF Levels	87
Figure 14(g) Location 10: Measured Environmental RF Levels	88
Figure 14(h) Location 10: Measured Environmental RF Levels	89



Introduction

This appendix documents measurement results from a preconstruction electromagnetic survey of locations along the San Jose to Carlucci project extent corridor. The purpose of the survey was to: (1) provide a baseline characterization of the existing electromagnetic environment, (2) allow comparisons with the expected electromagnetic footprint from the planned California High-Speed Rail (HSR) system, and (3) provide guidance for electromagnetic compatibility (EMC) requirements by defining the typical electromagnetic environment that the HSR system must operate in without interference.

Land uses, existing facilities, and infrastructure along the alignment were reviewed, with a list of approximately 30 candidate sites evaluated. This review concentrated on identifying potentially electromagnetic interference (EMI)-sensitive facilities, as well as existing electromagnetic field (EMF) sources such as power generation, power distribution, and communications facilities. The selection criteria, taken from Technical Memorandum (TM) 3.4.11, Measurement Procedure for Assessment of CHSTP Alignment EMI Footprint, favored providing a balanced coverage of:

- The geographic extent of the segment
- High-emission sites
- Low-emission sites
- Sites with high-sensitivity receptors

A final group consisting of 10 sites was selected based upon the above considerations and to provide representative coverage of land uses. Two types of measurements were performed at each location. The first involved measurement of radiated electric fields from 10 kilohertz (kHz) to 6 gigahertz (GHz), meant to characterize the radio-frequency (RF) environment. These electric field strengths were measured using an RF spectrum analyzer and calibrated antennas. Expected sources of RF signals included:

- Cell towers (cellular telephone)
- Broadcast towers (radio and television broadcasts)
- Airport radars and aircraft communications equipment
- General high-frequency and very-high-frequency fixed and mobile communications systems (e.g., police, fire, emergency medical technician, utilities, and government)
- Local wireless (wireless fidelity [WiFi] and Worldwide Interoperability for Microwave Access [WiMAX])

The second part of the test procedure involved measurements of background direct current (DC) and power frequency magnetic fields along the alignment. These magnetic fields were recorded using a three-axis fluxgate sensor with a waveform recording data acquisition system. Expected sources of DC and low-frequency magnetic fields included:

- The geomagnetic field
- High-voltage transmission lines
- Electric distribution lines
- Traction power distribution facilities
- Geomagnetic perturbations due to passing vehicles and trains

The facilities most sensitive to shifts in the DC (geomagnetic perturbations) and alternating current (AC) magnetic fields are:

- High technology semiconductor (e.g., electron microscopes [transmission electron microscopes/scanning electron microscopes], electron-beam lithography, ion-writing systems, focused ion-beam systems)
- High technology biology (e.g., nuclear magnetic resonance, magnetic resonance imaging [MRI], electron microscopes)



- Medical imaging (e.g., computed tomography [CT] scanners, MRI systems)
- University/research (instrumentation for chemistry, physics, electrical engineering, and similar systems to those mentioned for high technology and medical facilities).

Test Procedures and Equipment

Analysts characterized the RF environment along the project extent by measuring the prevailing electric field strength at each of the 10 test sites, over the frequency range from 10 kHz to 6 GHz. The RF and magnetic field measurements were performed between July 18, 2016, and July 22, 2016. Measurements were made using a vertical monopole antenna (AH Systems SAS-550-1) for the frequency range from 10 kHz to 30 MHz and a broadband bilogical antenna (AH Systems SAS-551-7) for the frequency range from 25 MHz to 6 GHz, connected to an Anritsu MS2721B Spectrum Analyzer. Measurements were made in eight contiguous frequency bands and recorded per Section 6.4 of TM 3.4.11. Where practical, the RF antennas were located approximately 50 feet from the proposed alignment.

Electric field measurement files from the spectrum analyzer include both min-hold and max-hold levels as a function of frequency across each of the measurement bands, and a complete file set will be preserved for each measurement location. Reported results include the low-frequency measurements with the omni-directional vertical monopole, plus measurements with the bilogical antenna in both horizontal and vertical positions, first facing the proposed alignment, and then in the direction that exhibited the maximum signal strength in each measurement band.

The magnetic field measurements characterized the prevailing background magnetic field levels, as well as the temporal variations caused by the passing of trains on the existing right-of-way. Measurements were made at two positions at each site, separated by approximately 30 feet. The magnetic field measurements were performed using a pair of three-axis 5 gauss Bartington fluxgate sensors (bandwidth DC to 3 kHz), connected to a National Instruments data acquisition system. Magnetic field waveforms were recorded so that DC and full frequency information is available over the entire sensor bandwidth.

Overview of the Measurement Results

Magnetic Fields

The measured DC magnetic field strengths ranged from 388 milligauss (mG) to 488 mG across the 10 measurement sites. At individual sites, the difference in DC field strength between the two sensors ranged from 15 to 46 mG. These differentials typically are the result of the influence from passing vehicles or nearby steel objects.

AC magnetic field strengths at the 10 sites varied over a range of more than three orders of magnitude, from 0.009 mG to 47 mG. The levels depend almost entirely on a site's proximity to power lines (medium-voltage distribution and high-voltage transmission lines) and other electrical system infrastructure. Such a wide range in observed magnetic field strengths is expected, given the variable levels of development along the project extent.

Figure 1 provides an illustration of the measured AC magnetic field strengths for three representative measurement sites: rural (Los Banos, Site 10), suburban (Gilroy, Site 8), and in close proximity to high-voltage transmission lines (Coyote, Site 5). These sites encompass the full range of observed 60 hertz (Hz) magnetic field levels, with Site 10 the lowest, Site 5 the highest, and Site 6 representing the median level. Levels are plotted for the 60 Hz fundamental.






Figure 1 Average Measured AC Magnetic Field Strengths

Electric Fields

Because of the very broad range of frequencies of interest, the electric field measurements at each site were divided into eight overlapping frequency bands to provide adequate frequency resolution in each band. Table 1 summarizes the maximum magnitude of the measured electric field values by frequency band for each site. The maximum electric fields strengths in bands B0 through B4 varied considerably across sites. Except for band B2 (the AM broadcast band), levels spanned a 30 decibel (dB) range. Even greater variation was seen at higher frequencies (bands B5 through B7), reflecting stronger differences in spectrum usage along the project alignment. Measured maximum levels in these bands varied by up to 45 dB. Variations of this magnitude are not unexpected when encompassing the range of urban, suburban, and rural settings found in the project extent.

Measurement Site San Jose Diridon Station A	B0 10-50 kHz	B1 50-550 KHz	B2 .50-3.0 MHz	B3 2.5-7.5 MHz	B4 5.0-30 MHz	B5 25- 200 MHz	B6 0.20- 2.2 GHz	B7 2.0- 6.0 GHz
1 – San Jose (urban)	135.1	128.4	143.5	128.4	101.7	119.0	122.9	114.4
		-		-	-		-	
2 – San Jose (urban)	146.7	124.4	145.0	122.5	97.1	110.6	118.7	112.3
Monterey Corridor Subsect	ion							
3 – San Jose (urban)	138.5	129.8	145.3	130.0	108.2	93.7	102.4	102.2
4 – San Jose (urban)	128.6	115.1	135.2	109.6	100.8	123.5	110.7	96.3
Morgan Hill and Gilroy Sub	section							
5 – Coyote (rural)	154.8	143.7	144.0	118.6	102.8	117.6	107.4	74.3
6 – Morgan Hill (rural)	134.7	113.5	135.1	96.9	83.7	96.8	119.0	105.5
7 – Gilroy (suburban)	133.5	127.1	142.5	123.6	88.8	102.9	102.4	103.5



Measurement Site	B0 10-50 kHz	B1 50-550 KHz	B2 .50-3.0 MHz	B3 2.5-7.5 MHz	B4 5.0-30 MHz	B5 25- 200 MHz	B6 0.20- 2.2 GHz	B7 2.0- 6.0 GHz			
Pacheco Pass Subsection											
8 – Hollister (rural)	128.1	119.8	136.1	109.8	84.9	82.7	90.6	68.9			
San Joaquin Valley Subsection											
9 - Santa Nella (rural)	141.1	122.9	139.1	117.0	86.9	80.0	102.3	92.5			
10 –Los Banos (rural)	148.4	131.3	134.7	112.3	107.4	83.9	80.4	69.8			


Field strength values are in decibel (dB), referenced to 1 microvolt meter/MHz.

GHz = gigahertz

KHz = kilohertz

MHz = megahertz

Figure 2 graphically shows the maximum measured electric field strengths by frequency band for the 10 measurement sites. Typical spectrum uses in each frequency band are also indicated in Figure A3.5-2. Increasing distance from the plot origin indicates higher field strength. Figure 3 shows the variance in RF field strengths across the measurement sites by frequency band. Standard deviations ranged from 4.5 dB in band B2 to as great as 17 dB in band B7.



JANUARY 2019

Figure 2 Maximum Electric Field Strengths by Frequency Band






Figure 3 Variation in Measured Maximum Electric Field Strengths

The 10 panels in Figure A3.5-4 graphically show the tabulated electric field strength values from Table A3.5-1.






Figure 4 Maximum Measured Electric Field Strengths

Individual Site Observations

The following discussion very briefly summarizes the EMF measurements conducted at each site. Complete measurement results are plotted and tabulated in the following section.

Site 1 (Newhall Street / Newhall Drive)

This measurement site was near Avaya Stadium. DC magnetic fields were quiet at this location. AC magnetic fields were due to overhead distribution lines. Magnetic fields show some variation due to varying load currents on the power lines, including a step change near the middle.

Site 2 (Montgomery Street / Otterson Street)

This location was South of Diridon Station adjacent to the Pacific Gas and Electric Company (PG&E) Distribution Substation. DC magnetic fields were relatively constant with very small variations. The first sensor had a total magnitude comparable to expected ambient, but the second was lower, indicating influence from nearby steel objects. Multiple trains moved along the alignment, but on the opposite side of the substation, they were sufficiently distant for the DC fluctuations to be quite small. AC magnetic fields in the 10-20 mG range are produced by the substation bus conductors and the power lines connected to the substation.



Site 3 (Communications Hill Boulevard / Curtner Avenue)

Measurements were made near Communications Hill, in a park adjacent to the project extent alignment. Both DC and AC magnetic fields were relatively quiet. DC magnetic fields were comparable in magnitude to the expected geomagnetic ambient level, with a few small variations due to pedestrians in the park passing very near the sensors (e.g., cell phones, strollers). There were no nearby power lines or underground circuits.

Site 4 (Great Oaks Parkway / Las Colinas Road)

This measurement site is immediately adjacent to tracks along Great Oak Parkway. DC magnetic field magnitudes were at expected ambient levels, with many small variations due to passing vehicles on Great Oak Parkway. AC magnetic fields were from overhead distribution lines on the opposite site of the tracks.

Site 5 (Metcalf Road / Coyote Ranch Road)

Measurements were made in front of PG&E Station. Spikes in DC magnetic fields were from passing vehicles along the adjacent road. AC fields were predominantly from the overhead transmission lines—four circuits on two sets of steel lattice towers—with magnitudes of nearly 50 mG at both sensors.

Site 6 (Railroad Avenue / Barrett Avenue)

This measurement site is in Morgan Hill, along Railroad Avenue, across from tracks. The DC magnetic fields were relatively constant with a few spikes due to passing vehicles. AC magnetic fields were less than 1 mG, with overhead distribution lines on the opposite side of the street along the tracks.

Site 7 (Monterey Highway / Las Animas Avenue)

This measurement site is in Gilroy on a cul-de-sac off Las Animas Avenue. This is a quiet area with constant DC magnetic fields and very low AC fields. Adjacent fields are used for livestock grazing. An overhead distribution line runs along the tracks.

Site 8 (State Route 152 / Casa de Fruta Parkway)

This measurement site is on Casa de Fruta Parkway, adjacent to State Route (SR) 152. This is a quiet area with virtually no DC magnetic field variations and essentially zero AC magnetic fields. There were no nearby AC power lines or sources.

Site 9 (Santa Nella Avenue / Fahey Road)

This measurement site is an agricultural area along Santa Nella Road. There were small DC field variations due to vehicles on SR 33. AC fields were in the 1-2 mG range due to distribution lines. AC fields showed variation over time.

Site 10 (Henry Miller Road / Carlucci Road)

Measurements were taken in an agricultural area northeast of Los Banos along Henry Miller Road. DC magnetic field spikes were due to passing trucks. AC fields were quite low. There was a distribution line to the south side of the sensor positions. A shift of the AC fields occurred for several minutes followed by a quick transient, most likely due to a load change on the distribution line such as running of pumps for irrigation.

Site Photographs and Measurement Data

The remainder of this appendix contains photographs and measurement results from each site.



JANUARY 2020

Figure 5(a) Location 1: Newhall Street / Newhall Drive, San Jose



Industrial/commercial area near the existing rail alignment, Avaya Stadium, and San Jose International airport (Lat 37.347447°, -121.923012°)



JANUARY 2019

Figure 5(b) Location 1: Measurement Location and Site Views



Photos depicting the site from the perspective of the RF measurement location. In the center is a satellite view, indicating the alignment (green line) and measurement points (red = RF, magenta = magnetometers). The satellite view is rotated so that the image at 0° faces the alignment.



JANUARY 2019


Figure 5(c) Location 1: Local EMF Sources

Nearby emitters include cell towers, distribution lines parallel and perpendicular to the alignment, and a small electrical substation. Photos depict visible close-proximity emitters. Other emissions sources may exist, but are not visible from the site.






DC Magnetic Field Measurement Statistics										
	B Horizo	ntal (mG)	B Vertio	cal (mG)	B Tota	ıl (mG)				
	Sensor 1	Sensor 2	Sensor 1	Sensor 2	Sensor 1	Sensor 2				
Max	242.1	249.6	378.0	361.2	448.7	439.0				
Median	241.8	249.4	377.9	361.0	448.6	438.8				
Min	241.7	249.2	377.6	360.0	448.5	437.9				
Range	0.4	0.5	0.4	1.3	0.2	1.1				
Std Dev	0.1	0.1	0.0	0.2	0.0	0.2				





	rms AC Magnetic Field Measurement Statistics															
	Fund 60	Hz (mG)	2nd	(mG)	3rd (mG)	4th (mG)	5th (mG)	6th (mG)	7th (mG)	Total A	C (mG)
	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor
	1	2	1	2	1	2	1	2	1	2	1	2	1	2	1	2
Max	5.910	6.109	0.023	0.034	0.110	0.116	0.019	0.058	0.494	0.543	0.021	0.027	0.098	0.099	5.925	6.127
Median	5.018	5.214	0.011	0.013	0.090	0.094	0.009	0.011	0.439	0.481	0.009	0.011	0.028	0.032	5.041	5.241
Min	4.709	4.891	0.002	0.003	0.068	0.071	0.002	0.003	0.364	0.388	0.002	0.002	0.008	0.008	4.733	4.920
Range	1.201	1.218	0.021	0.030	0.042	0.045	0.018	0.056	0.130	0.155	0.019	0.025	0.090	0.092	1.192	1.207
Std Dev	0.396	0.394	0.003	0.004	0.008	0.006	0.003	0.006	0.023	0.028	0.003	0.003	0.022	0.022	0.393	0.390


Figure 5(d) Location 1: AC and DC Magnetic Field Measurement Results
















	Maximum Levels												
Band number	Freq. Range (MHz)	Pk Min-Hold (dB uV/m/MHz)	@ Freq. (MHz)	Pk Max-Hold (dB uV/m/MHz)	@ Freq. (MHz)								
B0	0.01 ~ 0.05	118.8	0.0301	135.1	0.0500								
B1	0.05 ~ 0.55	103.8	0.3518	128.4	0.3600								
B2	0.50 ~ 3.00	130.1	1.1682	143.5	1.1682								
B3	2.5 ~ 7.5	102.3	2.6636	128.4	2.6727								
B4	5 ~ 30	77.8	5.0000	101.7	5.0000								


Figure 5(e) Location 1: Measured Environmental RF Levels


Non-Directional Data from Vertically Oriented Monopole Antenna, Bands 0-4












	Maximum Levels												
	Freq.		Ver	tical			Horiz	zontal					
Band	Range	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.				
number	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)				
B5	25~200	102.1	105.727	110.6	161.727	97.7	105.727	119.0	161.727				
	JANUARY 2019												

Figure 5(f) Location 1: Measured Environmental RF Levels

Band 5 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation







	Maximum Levels													
	Freq.		Ver	tical		Horizontal								
	Range	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.					
Ba	nd (MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)					
B	6 200 ~ 2200	114.6	887.273	122.9	890.909	113.0	887.273	119.3	890.909					
	JANUARY 2019													


Figure 5(g) Location 1: Measured Environmental RF Levels

Band 6 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation









	Maximum Levels								
			Ver	tical		Horizontal			
	Freq. Range	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.
Band	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)
B7	2000~6000	107.6	2116.364	114.4	2116.364	107.2	2123.636	113.3	2130.909

JANUARY 2019

Figure 5(h) Location 1: Measured Environmental RF Levels

Band 7 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation






Figure 6(a) Location 2: Montgomery Street / Otterson Street, San Jose

Industrial/commercial setting between San Jose Diridon Station and the PG&E substation (Lat 37.328142°, Lon -121.902140°)

California High-Speed Rail Authority

April 2020



Figure 6(b) Location 2: Measurement Location and Site Views

Photos depicting the site from the perspective of the RF measurement location. In the center is a satellite view, indicating the alignment (green line) and measurement points (red = RF, magenta = magnetometers). The satellite view is rotated so that the image at 0° faces the alignment.

April 2020






Figure 6(c) Location 2: Local EMF Sources

Nearby emitters include high-voltage transmission lines and substation equipment, distribution lines, and cellular communications. Photos depict visible close-proximity emitters. Other emissions sources may exist, but are not visible from the site.


California High-Speed Rail Authority

San Jose to Merced Project Section Draft EIR/EIS





DC Magnetic Field Measurement Statistics									
	B Horizo	ntal (mG)	B Vertic	al (mG)	B Total (mG)				
	Sensor 1	Sensor 2	Sensor 1	Sensor 2	Sensor 1	Sensor 2			
Max	289.7	222.9	325.5	319.5	434.9	389.1			
Median	288.9	222.2	324.1	318.4	434.2	388.2			
Min	288.2	221.0	322.3	314.1	432.5	384.4			
Range	1.5	1.9	3.2	5.5	2.4	4.7			
Std Dev	0.2	0.4	0.3	0.5	0.2	0.4			




					r	ms AC Ma	agnetic Fi	eld Meası	irement S	tatistics						
	Fund 60Hz (mG)		G) 2nd (mG)		3rd (mG)		4th (mG)		5th (mG)		6th (mG)	7th (mG)		Total AC (mG)	
	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor
	1	2	1	2	1	2	1	2	1	2	1	2	1	2	1	2
Max	14.402	23.718	0.107	0.229	2.078	4.397	0.073	0.092	0.699	0.727	0.076	0.244	0.314	0.488	14.556	24.043
Median	13.072	20.533	0.037	0.083	2.004	4.079	0.015	0.033	0.629	0.550	0.018	0.090	0.275	0.380	13.241	20.946
Min	11.594	18.948	0.007	0.010	1.937	3.729	0.003	0.006	0.576	0.381	0.005	0.019	0.231	0.303	11.791	19.387
Range	2.808	4.770	0.100	0.219	0.141	0.668	0.070	0.087	0.122	0.347	0.071	0.225	0.082	0.185	2.765	4.656
Std Dev	0.552	0.719	0.013	0.038	0.023	0.086	0.006	0.014	0.017	0.058	0.006	0.030	0.010	0.024	0.543	0.706

Figure 6(d) Location 2: AC and DC Magnetic Field Measurement Results


California High-Speed Rail Authority


April 2020















	Maximum Levels									
Band number	Freq. Range (MHz)	Pk Min-Hold (dB uV/m/MHz)	@ Freq. (MHz)	Pk Max-Hold (dB uV/m/MHz)	@ Freq. (MHz)					
B0	0.01 ~ 0.05	118.7	0.0138	146.7	0.0170					
B1	0.05 ~ 0.55	104.0	0.3591	124.4	0.3600					
B2	0.50 ~ 3.00	132.7	1.1727	145.0	1.1682					
B3	2.5 ~ 7.5	97.5	2.5364	122.5	2.7636					
B4	5 ~ 30	71.2	25.2727	97.1	5.0909					

Figure 6(e) Location 2: Measured Environmental RF Levels

Non-Directional Data from Vertically Oriented Monopole Antenna, Bands 0-4






	Maximum Levels								
			Ve	rtical		Horizontal			
Band	Freq. Range	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.
number	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)
B5	25 ~ 200	108.5	105.727	110.6	105.727	106.3	105.727	108.6	105.727

Figure 6(f) Location 2: Measured Environmental RF Levels

Band 5 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation





Maximum Levels									
		Verti	cal		Horizontal				
Freq. Range	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.	
(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	
200 ~ 2200	107.1	1960.000	118.7	930.909	112.7	1960.000	114.2	1960.000	
	(MHz)	(MHz) (dBuV/m/MHz)	Freq. Range Pk Min-Hold @ Freq. (MHz) (dBuV/m/MHz) (MHz)	Freq. Range Pk Min-Hold @ Freq. Pk Max-Hold (MHz) (dBuV/m/MHz) (MHz) (dBuV/m/MHz)	Freq. Range Pk Min-Hold @ Freq. Pk Max-Hold @ Freq. (MHz) (dBuV/m/MHz) (MHz) (dBuV/m/MHz) (MHz)	Vertical Freq. Range Pk Min-Hold @ Freq. Pk Max-Hold @ Freq. Pk Min-Hold (MHz) (dBuV/m/MHz) (MHz) (dBuV/m/MHz) (dBuV/m/MHz) (dBuV/m/MHz)	Vertical Horiz Freq. Range Pk Min-Hold @ Freq. Pk Max-Hold @ Freq. Pk Min-Hold @ Freq. (MHz) (dBuV/m/MHz) (MHz) (dBuV/m/MHz) (MHz) (dBuV/m/MHz) (MHz)	Vertical Horizontal Freq. Range Pk Min-Hold @ Freq. Pk Max-Hold @ Freq. Pk Min-Hold @ Freq. Pk Max-Hold (MHz) (dBuV/m/MHz) (dBuV/m/MHz) (dBuV/m/MHz) (MHz) (dBuV/m/MHz) (dBuV/m/MLz)	

JANUARY 2019

Figure 6(g) Location 2: Measured Environmental RF Levels

Band 6 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation

3.5-A-25 | Page






Figure 6(h) Location 2: Measured Environmental RF Levels

Band 7 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation






Figure 7(a) Location 3: Communications Hill Boulevard/Monte Vista Drive, San Jose

Suburban setting near the existing rail alignment, with significant RF emitters (Lat 37.293722°, Lon -121.865194°)

California High-Speed Rail Authority

San Jose to Merced Project Section Draft EIR/EIS





JANUARY 2019

Figure 7(b) Location 3: Measurement Location and Site Views

Photos depicting the site from the perspective of the RF measurement location. In the center is a satellite view, indicating the alignment (green line) and measurement points (red = RF, magenta = magnetometers). The satellite view is rotated so that the image at 0° faces the alignment.





Figure 7(c) Location 3: Local EMF Sources


Nearby emitters include microwave towers, railway communications, and fixed land communications.

Photos depict visible close-proximity emitters. Other emissions sources may exist that are not readily visible from the site.


California High-Speed Rail Authority

San Jose to Merced Project Section Draft EIR/EIS






	B Horizo	ntal (mG)	B Vertio	cal (mG)	B Total (mG)					
	Sensor 1		Sensor 1	Sensor 1 Sensor 2		Sensor 2				
Max	248.0	202.6	368.6	413.8	444.1	460.6				
Median	247.7	201.2	368.5	412.9	444.0	459.2				
Min	247.4	198.7	368.3	411.7	443.8	458.3				
Range	0.5	3.9	0.3	2.2	0.2	2.3				
Std Dev	0.1 0.8		0.1	0.3	0.0	0.2				





	rms AC Magnetic Field Measurement Statistics															
	Fund 60Hz (mG)		2nd (mG)		3rd (mG)		4th (mG)		5th (mG)		6th (I	mG)	7th (mG)		Total AC (mG	
	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor
	1	2	1	2	1	2	1	2	1	2	1	2	1	2	1	2
Max	0.028	0.030	0.019	0.020	0.031	0.032	0.020	0.028	0.022	0.026	0.020	0.022	0.021	0.024	0.044	0.046
Median	0.016	0.016	0.008	0.008	0.020	0.020	0.008	0.009	0.009	0.010	0.009	0.009	0.009	0.010	0.033	0.034
Min	0.004	0.004	0.002	0.002	0.008	0.007	0.002	0.002	0.002	0.002	0.002	0.001	0.001	0.003	0.022	0.023
Range	0.024	0.027	0.018	0.018	0.023	0.024	0.018	0.026	0.020	0.024	0.018	0.021	0.020	0.021	0.022	0.023
Std Dev	0.003	0.004	0.002	0.003	0.003	0.004	0.002	0.003	0.003	0.003	0.003	0.003	0.003	0.003	0.003	0.003


Figure 7(d) Location 3: Measured DC and AC Magnetic Field Strengths
















	Maximum Levels								
Band	Freq. Range	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.				
number	(MHz)	(dB uV/m/MHz)	(MHz)	(dB uV/m/MHz)	(MHz)				
B0	0.01 ~ 0.05	115.7	0.0140	138.5	0.0120				
B1	0.05 ~ 0.55	104.6	0.4273	129.8	0.4200				
B2	0.50 ~ 3.00	130.5	1.1682	145.3	1.1682				
B3	2.5 ~ 7.5	107.7	2.6727	130.0	2.7636				
B4	5 ~ 30	92.4	5.0909	108.2	5.8636				


Figure 7(e) Location 3: Measured Environmental RF Levels Non-Directional Data from Vertically Oriented Monopole Antenna, Bands 0-4


April 2020














	Maximum Levels									
			Ver	tical		Horizontal				
	Freq.		0		@		0		@	
Band	Range	Pk Min-Hold	Freq.	Pk Max-Hold	Freq.	Pk Min-Hold	Freq.	Pk Max-Hold	Freq.	
number	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	
B5	25 ~ 200	89.6	105.727	93.7	105.727	90.5	105.727	92.4	105.727	


Figure 7(f) Location 3: Measured Environmental RF Levels Band 5 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation












	Maximum Levels									
			Ver	tical		Horizontal				
	Freq.		0		0		0			
	Range	Pk Min-Hold	Freq.	Pk Max-Hold	Freq.	Pk Min-Hold	Freq.	Pk Max-Hold	@ Freq.	
Band	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	
B6	200 ~ 2200	97.4	770.909	102.4	774.545	79.8	774.545	87.2	774.545	

Figure 7(g) Location 3: Measured Environmental RF Levels Band 6 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation

California High-Speed Rail Authority

April 2020 3.5-A-33 | Page





(101112)		(101112)
2690.909	75.1	2436.364
	JAN	UARY 2019

Figure 7(h) Location 3: Measured Environmental RF Levels Band 7 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation

2421.818

66.8

California High-Speed Rail Authority

B7

2000~6000

66.3

2712.727

102.2





Figure 8(a) Location 4: Great Oaks Parkway/Las Colinas Road, San Jose

Adjacent to high technology office park and near the existing rail; no visible RF emitters (Lat 37.239322°, Lon -121.776080°)





JANUARY 2019

Figure 8(b) Location 4: Measurement Location and Site Views

Photos depicting the site from the perspective of the RF measurement location. In the center is a satellite view, indicating the alignment (green line) and measurement points (red = RF, magenta = magnetometers). The satellite view is rotated so that the image at 0° faces the alignment.

April 2020






JANUARY 2019

Figure 8(c) Location 4: Local EMF Sources


Nearby emitters included a single local distribution line.

Photos depict visible close-proximity emitters. Other emissions sources may exist, but are not visible from the site.





	D	C Magnetic Fi	eld Measuren	nent Statistics	;			
	B Horizo	ntal (mG)	B Vertic	al (mG)	B Total (mG)			
	Sensor 1	Sensor 2	Sensor 1	Sensor 2	Sensor 1	Sensor 2		
Max	245.1	254.0	412.4	389.9	479.1	465.0		
Median	242.4 251.9		411.9	389.6	478.0	463.9		
Min	240.0	249.6	411.1	388.4	476.4	462.6		
Range	Range 5.1 4.4		1.3	1.5	2.7	2.4		
Std Dev	0.2	0.1	0.1	0.2	0.1	0.2		





	rms AC Magnetic Field Measurement Statistics															
	Fund 60	Hz (mG)	z (mG) 2nd (mG)		3rd (mG)		4th (mG)	5th ((mG)	6th (mG)	7th (mG)		Total AC (mG)	
	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor
	1	2	1	2	1	2	1	2	1	2	1	2	1	2	1	2
Max	0.990	0.916	0.023	0.024	1.488	1.443	0.025	0.027	0.162	0.155	0.030	0.029	0.075	0.072	1.740	1.664
Median	0.722	0.657	0.011	0.011	1.446	1.402	0.012	0.012	0.135	0.127	0.015	0.015	0.059	0.057	1.624	1.558
Min	0.557	0.507	0.002	0.002	1.381	1.340	0.003	0.002	0.107	0.094	0.004	0.004	0.044	0.043	1.541	1.485
Range	0.433	0.409	0.021	0.021	0.107	0.104	0.022	0.025	0.056	0.061	0.026	0.025	0.032	0.029	0.199	0.179
Std Dev	0.097	0.093	0.003	0.003	0.020	0.020	0.004	0.004	0.009	0.009	0.004	0.004	0.004	0.004	0.037	0.034


Figure 8(d) Location 4: AC and DC Magnetic Field Measurement Results














	Maximum Levels												
Band	Freq. Range	Pk Min-Hold	Min-Hold @ Freq. Pk Max-Ho										
number	(MHz)	(dB uV/m/MHz)	(MHz)	(dB uV/m/MHz)	(MHz)								
B0	0.01 ~ 0.05	100.1	0.0213	128.6	0.0146								
B1	0.05 ~ 0.55	94.7	0.0591	115.1	0.1700								
B2	0.50 ~ 3.00	120.8	1.1682	135.2	1.1727								
B3	2.5 ~ 7.5	86.1	2.9818	109.6	3.3818								
B4	5 ~ 30	90.4	14.2273	100.8	14.2273								


Figure 8(e) Location 4: Measured Environmental RF Levels Non-Directional Data from Vertically Oriented Monopole Antenna, Bands 0-4


California High-Speed Rail Authority


April 2020 3.5-A-39| Page













	Maximum Levels													
	Freq.		Ver	tical	Horizontal									
Band	Range	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.					
number	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)					
B5	25 ~ 200	120.5	92.273	123.5	92.273	119.5	92.273	122.5	92.273					


Figure 8(f) Location 4: Measured Environmental RF Levels


Band 5 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation











				Maximur	n Levels							
	Freq.		Ver	tical		Horizontal						
	Range	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.			
Band	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)			
B6	200 ~ 2200	103.7	730.909	110.7	734.545	98.5	887.273	105.4	890.909			

JANUARY 2019

Figure 8(g) Location 4: Measured Environmental RF Levels

Band 6 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation






Figure 8(h) Location 4: Measured Environmental RF Levels

Band 7 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation




Figure 9(a) Location 5: Metcalf Energy Center, San Jose

Adjacent to the PG&E Metcalf Substation (Lat 37.223022°, Lon -121.744592°)

California High-Speed Rail Authority

San Jose to Merced Project Section Draft EIR/EIS





Figure 9(b) Location 5: Measurement Location and Site Views

Photos depicting the site from the perspective of the RF measurement location. In the center is a satellite view, indicating the alignment (green line) and measurement points (red = RF, magenta = magnetometers). The satellite view is rotated so that the image at 0° faces the alignment.






Figure 9(c) Location 5: Local EMF Sources

Immediately adjacent to the PG&E Substation. Nearby emitters include high-voltage transmission lines and substation equipment Photos depict visible close-proximity emitters. Other emissions sources are assumed to exist, but are not visible from the site.


California High-Speed Rail Authority

San Jose to Merced Project Section Draft EIR/EIS






	D	DC Magnetic Field Measurement Statistics													
	B Horizo	ntal (mG)	B Vertic	al (mG)	B Tota	l (mG)									
	Sensor 1	Sensor 2	Sensor 1	Sensor 2	Sensor 1	Sensor 2									
Max	244.0	241.9	398.1	381.9	463.3	448.6									
Median	235.8	234.1	397.8	381.4	462.5	447.4									
Min	232.0	228.3	382.4	358.9	451.8	431.1									
Range	12.0	13.5	15.7	23.0	11.5	17.6									
Std Dev	0.3	0.4	0.4	0.7	0.3	0.6									



	rms AC Magnetic Field Measurement Statistics															
	Fund 60	Hz (mG)	2nd (mG)		3rd (mG)		4th (mG)	5th (mG)		6th (mG)		7th (mG)		Total AC (mG)	
	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor
	1	2	1	2	1	2	1	2	1	2	1	2	1	2	1	2
Max	47.175	48.472	0.075	0.105	1.282	1.630	0.074	0.070	0.248	0.255	0.087	0.089	0.232	0.223	47.192	48.499
Median	46.512	47.805	0.017	0.023	1.226	1.578	0.016	0.014	0.200	0.215	0.034	0.032	0.175	0.167	46.529	47.832
Min	46.002	47.107	0.003	0.005	1.186	1.543	0.003	0.003	0.163	0.184	0.014	0.010	0.150	0.140	46.019	47.135
Range	1.173	1.364	0.072	0.100	0.096	0.086	0.071	0.067	0.085	0.072	0.072	0.079	0.082	0.083	1.173	1.364
Std Dev	0.174	0.189	0.007	0.009	0.018	0.015	0.005	0.005	0.006	0.007	0.007	0.007	0.007	0.007	0.174	0.189

Figure 9(d) Location 5: AC and DC Magnetic Field Measurement Results







	Maximum Levels												
Band	Freq. Range	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.								
number	(MHz)	(dB uV/m/MHz)	(MHz)	(dB uV/m/MHz)	(MHz)								
B0	0.01 ~ 0.05	81.0	0.0101	154.8	0.0118								
B1	0.05 ~ 0.55	51.5	0.1327	143.7	0.0745								
B2	0.50 ~ 3.00	61.6	0.8091	144.0	0.8091								
B3	2.5 ~ 7.5	49.8	5.8182	118.6	3.0182								
B4	5 ~ 30	35.6	12.0455	102.8	12.0455								


Figure 9(e) Location 5: Measured Environmental RF Levels


Non-Directional Data from Vertically Oriented Monopole Antenna, Bands 0-4











	Maximum Levels													
			Ver	tical		Horizontal								
	Freq.		0		0		@		@					
Band	Range	Pk Min-Hold	Freq.	Pk Max-Hold	Freq.	Pk Min-Hold	Freq.	Pk Max-Hold	Freq.					
number	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)					
B5	25 ~ 200	113.0	92.273	117.6	92.273	113.4	92.273	115.9	92.273					

Figure 9(f) Location 5: Measured Environmental RF Levels

Band 5 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation






Figure 9(g) Location 5: Measured Environmental RF Levels

Band 6 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation

April 2020






Figure 9(h) Location 5: Measured Environmental RF Levels

Band 7 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation





Figure 10(a) Location 6: Railroad Avenue/Barrett Avenue, Morgan Hill

Commercial area across from Morgan Hill Police Department, (Lat 37.118225°, Lon -121.638550°)

California High-Speed Rail Authority

San Jose to Merced Project Section Draft EIR/EIS





Figure 10(b) Location 6: Measurement Location and Site Views

Photos depicting the site from the perspective of the RF measurement location. In the center is a satellite view, indicating the alignment (green line) and measurement points (red = RF, magenta = magnetometers). The satellite view is rotated so that the image at 0° faces the alignment.




Figure 10(c) Location 6: Local EMF Sources


Nearby emitters include cell towers, fixed land communications, and distribution lines parallel to the alignment.

Photos depict visible close-proximity emitters. Other emissions sources may exist that are not readily visible from the site.





	DC Magnetic Field Measurement Statistics												
	B Horizo	ntal (mG)	B Vertic	al (mG)	B Total (mG)								
	Sensor 1	Sensor 2	Sensor 1	Sensor 2	Sensor 1	Sensor 2							
Max	221.7	239.2	416.6	393.8	470.9	456.9							
Median	219.5	227.1	416.3	393.3	470.6	454.2							
Min	216.6	226.0	413.9	389.3	468.8	451.8							
Range	Range 5.1		2.7	4.5	2.1	5.1							
Std Dev	Std Dev 0.2		0.1	0.2	0.1	0.2							




	rms AC Magnetic Field Measurement Statistics															
	Fund 60	Hz (mG)	z (mG) 2nd (mG)		3rd (mG)		4th (4th (mG)		mG)	6th (mG)		7th (mG)		Total AC (mG)	
	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor
	1	2	1	2	1	2	1	2	1	2	1	2	1	2	1	2
Max	0.808	0.786	0.065	0.206	0.469	0.476	0.068	0.105	0.107	0.102	0.075	0.072	0.094	0.092	0.902	0.891
Median	0.528	0.516	0.010	0.010	0.417	0.389	0.010	0.010	0.046	0.044	0.012	0.012	0.041	0.036	0.673	0.647
Min	0.359	0.354	0.003	0.002	0.375	0.345	0.001	0.002	0.028	0.023	0.003	0.002	0.025	0.019	0.554	0.526
Range	0.449	0.432	0.062	0.204	0.094	0.131	0.066	0.104	0.079	0.078	0.073	0.070	0.069	0.073	0.348	0.365
Std Dev	0.067	0.065	0.006	0.006	0.012	0.013	0.007	0.007	0.008	0.008	0.010	0.009	0.009	0.009	0.053	0.052

Figure 10(d) Location 6: AC and DC Magnetic Field Measurement Results

California High-Speed Rail Authority

April 2020





12.8636

Figure 10(e) Location 6: Measured Environmental RF Levels

83.7

25.2727

Non-Directional Data from Vertically Oriented Monopole Antenna, Bands 0-4


78.0


California High-Speed Rail Authority


Β4


5~30











				Maximur	n Levels								
	Vertical Horizontal												
	Freq.		0		@		@		@				
Band	Range	Pk Min-Hold	Freq.	Pk Max-Hold	Freq.	Pk Min-Hold	Freq.	Pk Max-Hold	Freq.				
number	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)				
B5	25 ~ 200	95.1	94.455	96.8	94.455	85.4	106.455	88.1	106.455				


JANUARY 2019

Figure 10(f) Location 6: Measured Environmental RF Levels

Band 5 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation

3.5-A-56 | Page






ΙΔΝΙ	JARY	2010
JANU	JARI	2019

Figure 10(g) Location 6: Measured Environmental RF Levels

Band 6 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation





				Maximi	um Levels						
	Freq.		Ver	tical		Horizontal					
	Range	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.	Pk Min-Hold @ Freq.		Pk Max-Hold	@ Freq.		
Band	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)		
B7	2000~6000	95.3	2123.636	105.5	2669.091	84.1	2625.455	98.7	2625.455		

Figure 10(h) Location 6: Measured Environmental RF Levels

Band 7 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation

3.5-A-58 | Page





Figure 11(a) Location 7: Monterey Highway/Las Animas Avenue, Gilroy

Suburban setting, with relatively few local RF emitters (Lat 37.028851°, Lon -121.578510°)

California High-Speed Rail Authority

San Jose to Merced Project Section Draft EIR/EIS

April 2020






Figure 11(b) Location 7: Measurement Location and Site Views


Photos depicting the site from the perspective of the RF measurement location. In the center is a satellite view, indicating the alignment (green line) and measurement points (red = RF, magenta = magnetometers). The satellite view is rotated so that the image at 0° faces the alignment.




Figure 11(c) Location 7: Local EMF Sources

Nearby emitters include microwave towers, railway communications, and distribution lines parallel to the alignment. Photos depict visible close-proximity emitters. Other emissions sources may exist that are not readily visible from the site.





	D	C Magnetic Fi	ield Measuren	nent Statistics	•								
	B Horizo	B Horizontal (mG) B Vertical (mG) B Total (mG)											
	Sensor 1	Sensor 2	Sensor 1	Sensor 2	Sensor 1	Sensor 2							
Max	230.3	226.2	395.5	396.6	457.0	456.1							
Median	230.0	225.3	394.8	396.3	456.9	456.0							
Min	228.8	224.0	394.5	396.0	456.8	455.3							
Range	1.6	2.2	1.0	0.6	0.2	0.8							
Std Dev	0.2	0.5	0.1	0.2	0.1	0.2							



	rms AC Magnetic Field Measurement Statistics															
	Fund 60	Hz (mG)	2nd	(mG)	3rd (mG)	4th (mG) 5th (mG)		6th (mG)		7th (mG)		Total AC (mG)			
	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor
	1	2	1	2	1	2	1	2	1	2	1	2	1	2	1	2
Max	0.222	0.225	0.021	0.022	0.713	0.694	0.020	0.021	0.063	0.057	0.019	0.023	0.027	0.030	0.735	0.717
Median	0.135	0.139	0.008	0.009	0.694	0.674	0.009	0.009	0.045	0.043	0.010	0.010	0.014	0.014	0.709	0.691
Min	0.057	0.061	0.002	0.001	0.673	0.651	0.001	0.002	0.030	0.027	0.002	0.002	0.002	0.003	0.687	0.664
Range	0.165	0.164	0.019	0.021	0.041	0.043	0.019	0.020	0.032	0.030	0.017	0.021	0.025	0.027	0.048	0.052
Std Dev	0.025	0.026	0.003	0.003	0.006	0.006	0.003	0.003	0.004	0.004	0.003	0.003	0.004	0.004	0.008	0.008

Figure 11(d) Location 7: AC and DC Magnetic Field Measurement Results









Figure 11(e) Location 7: Measured Environmental RF Levels


Non-Directional Data from Vertically Oriented Monopole Antenna, Bands 0-4












				Maximun	1 Levels								
			Vert	ical			Horiz	ontal					
	Freq.		0		@		@		@				
Band	Range	Pk Min-Hold	Freq.	Pk Max-Hold	Freq.	Pk Min-Hold	Freq.	Pk Max-Hold	Freq.				
number	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)				
B5	25~200	85.1	100.273	102.9	27.545	85.2	100.273	86.9	100.273				
	JANUARY 2019												

Figure 11(f) Location 7: Measured Environmental RF Levels

Band 5 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation






			Maximum Levels														
	Freq.		Ver	tical		Horizontal											
	Range Pk Min-Hold @ Fre		@ Freq.	Pk Max-Hold @ Freq.		Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.								
Band	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)								
B6	200 ~ 2200	94.9	2123.636	102.4	2127.273	90.9	883.636	97.5	887.273								

Figure 11(g) Location 7: Measured Environmental RF Levels

Band 6 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation





JANUARY	2019
JANUARI	2013

Figure 11(h) Location 7: Measured Environmental RF Levels

Band 7 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation





Figure 12(a) Location 8: SR 152/Casa de Fruta Parkway, Hollister

Rural setting adjacent to Casa de Fruta, no visible RF emitters (Lat 36.985247°, Lon -121.383899°)

California High-Speed Rail Authority

San Jose to Merced Project Section Draft EIR/EIS







Figure 12(b) Location 8: Measurement Location and Site Views

Photos depicting the site from the perspective of the RF measurement location. In the center is a satellite view, indicating the alignment (green line) and measurement points (red = RF, magenta = magnetometers). The satellite view is rotated so that the image at 0° faces the alignment.





	D	C Magnetic Fi	eld Measuren	nent Statistics									
	B Horizo	B Horizontal (mG) B Vertical (mG) B Total (mG)											
	Sensor 1	Sensor 2	Sensor 1	Sensor 2	Sensor 1	Sensor 2							
Max	227.4	212.4	417.2	396.9	474.8	450.1							
Median	226.8	212.2	416.9	396.8	474.6	449.9							
Min	226.2	211.2	416.5	395.9	474.4	448.8							
Range	1.1	1.2	0.7	0.9	0.4	1.4							
Std Dev	0.2	0.2	0.1	0.2	0.1	0.2							



	rms AC Magnetic Field Measurement Statistics															
	Fund 60	Hz (mG)	2nd	(mG)	3rd (mG)		4th (mG)		5th (mG)		6th (mG)		7th (mG)		Total AC (mG)	
	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor
	1	2	1	2	1	2	1	2	1	2	1	2	1	2	1	2
Max	0.018	0.023	0.019	0.021	0.019	0.018	0.020	0.020	0.018	0.021	0.020	0.022	0.023	0.027	0.035	0.035
Median	0.008	0.009	0.008	0.009	0.008	0.009	0.008	0.009	0.009	0.009	0.009	0.010	0.009	0.010	0.024	0.026
Min	0.002	0.002	0.002	0.002	0.002	0.001	0.001	0.002	0.002	0.002	0.002	0.002	0.002	0.002	0.015	0.017
Range	0.016	0.021	0.017	0.019	0.018	0.017	0.019	0.019	0.016	0.019	0.019	0.020	0.021	0.025	0.019	0.019
Std Dev	0.002	0.003	0.002	0.003	0.002	0.003	0.002	0.003	0.003	0.003	0.003	0.003	0.003	0.003	0.003	0.003

Figure 12(c) Location 8: AC and DC Magnetic Field Measurement Results






Figure 12(d) Location 8: Measured Environmental RF Levels

109.8

84.9

2.6364

25.2727

Non-Directional Data from Vertically Oriented Monopole Antenna, Bands 0-4

77.0

79.8

April 2020

California High-Speed Rail Authority

2.5818

24.8182


B3


Β4


2.5~7.5


5~30













	Maximum Levels													
	Vertical Horizontal													
	Freq.		@		@		0		@					
Band	Range	Pk Min-Hold	Freq.	Pk Max-Hold	Freq.	Pk Min-Hold	Freq.	Pk Max-Hold	Freq.					
number	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)					
B5	180.273	74.7	126.455											


Figure 12(e) Location 8: Measured Environmental RF Levels


Band 5 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation











	Maximum Levels													
Freq. Vertical Horizontal														
	Range	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.					
Band	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)					
B6	200 ~ 2200	84.9	1963.636	89.4	1963.636	87.4	1963.636	90.6	1963.636					

JANUARY 2019

Figure 12(f) Location 8: Measured Environmental RF Levels

Band 6 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation






Figure 12(h) Location 8: Measured Environmental RF Levels

Band 7 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation



Figure 13(a) Location 9: Santa Nella Avenue/Fahey Road, Santa Nella

Rural setting with no visible RF sources (Lat 37.126085°, Lon -121.015302°)





Figure 13(b) Location 9: Measurement Location and Site Views

Photos depicting the site from the perspective of the RF measurement location. In the center is a satellite view, indicating the alignment (green line) and measurement points (red = RF, magenta = magnetometers). The satellite view is rotated so that the image at 0° faces the alignment.






Figure 13(c) Location 9: Local EMF Sources


Nearby emitters include distribution lines perpendicular and parallel to the alignment.

Photos depict visible close-proximity emitters. Other emissions sources may exist, but are not visible from the site.





	D	C Magnetic Fi	ield Measuren	nent Statistics	;	
	B Horizo	ntal (mG)	B Vertic	al (mG)	B Tota	ıl (mG)
	Sensor 1	Sensor 2	Sensor 1	Sensor 2		
Max	237.7	274.5	418.8	394.3	481.2	479.4
Median	237.0	273.0	418.6	393.4	481.0	478.8
Min	235.7	271.5	417.8	391.0	480.0	476.6
Range	2.0	2.9	1.0	3.3	1.2	2.8
Std Dev	0.3	0.3	0.2	0.6	0.2	0.4



	rms AC Magnetic Field Measurement Statistics															
	Fund 60	Hz (mG)	2nd	(mG)	3rd (mG)	4th (mG)	5th ((mG)	6th (mG)	7th ((mG)	Total A	C (mG)
	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor
	1	2	1	2	1	2	1	2	1	2	1	2	1	2	1	2
Max	1.304	2.526	0.052	0.050	0.054	0.061	0.061	0.060	0.095	0.135	0.069	0.064	0.108	0.139	1.306	2.529
Median	1.096	2.127	0.010	0.010	0.018	0.026	0.010	0.010	0.046	0.092	0.011	0.011	0.056	0.103	1.098	2.131
Min	1.012	1.968	0.002	0.002	0.004	0.005	0.002	0.003	0.026	0.054	0.002	0.003	0.031	0.072	1.015	1.974
Range	0.293	0.558	0.050	0.048	0.050	0.056	0.059	0.057	0.069	0.081	0.067	0.061	0.077	0.067	0.291	0.555
Std Dev	0.057	0.108	0.003	0.003	0.005	0.009	0.004	0.004	0.006	0.010	0.004	0.004	0.007	0.010	0.057	0.107

Figure 13(d) Location 9: AC and DC Magnetic Field Measurement Results

April 2020









Figure 13(e) Location 9: Measured Environmental RF Levels


Non-Directional Data from Vertically Oriented Monopole Antenna, Bands 0-4












	Maximum Levels													
	Vertical Horizontal													
	Freq.		0		@		0		@					
Band	Range	Pk Min-Hold	Freq.	Pk Max-Hold	Freq.	Pk Min-Hold	Freq.	Pk Max-Hold	Freq.					
number	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)					
B5	25 ~ 200	76.7	106.818	106.818	70.6	106.818	73.4	106.818						

JANUARY 2019

Figure 13(f) Location 9: Measured Environmental RF Levels

Band 5 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation






	Maximum Levels														
	Freq. Vertical Horizontal														
	Range	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.						
Band	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)						
B6	200 ~ 2200	87.2	1934.545	102.3	1872.727	76.7	1989.091	91.1	927.273						

Figure 13(g) Location 9: Measured Environmental RF Levels

Band 6 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation





	Maximum Levels												
	Freq. Vertical Horizontal												
	Range	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.				
Band	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)				
B7	B7 2000~6000 88.2 2123.636 92.3 2123.636 80.6 2123.636 92.5 2130.909												

Figure 13(h) Location 9: Measured Environmental RF Levels

Band 7 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation





Figure 14(a) Location 10: Henry Miller Road/Carlucci Road, Dos Palos

Rural setting, with one cell tower approximately 3.5 miles distant (Lat 37.097787°, Lon -120.680892°)

California High-Speed Rail Authority

San Jose to Merced Project Section Draft EIR/EIS

April 2020





Figure 14(b) Location 10: Measurement Location and Site Views

Photos depicting the site from the perspective of the RF measurement location. In the center is a satellite view, indicating the alignment (green line) and measurement points (red = RF, magenta = magnetometers). The satellite view is rotated so that the image at 0° faces the alignment.






Figure 14(c) Location 10: Local EMF sources


Nearby emitters include distribution lines parallel and perpendicular to the alignment and a distant (3.5 mi) cell tower.

Photos depict visible close-proximity emitters. Other emissions sources may exist that are not readily visible from the site.





	DC Magnetic Field Measurement Statistics												
	B Horizo	ntal (mG)	B Vertic	al (mG)	B Tota	ıl (mG)							
	Sensor 1	Sensor 2	Sensor 1	Sensor 2	Sensor 1	Sensor 2							
Max	238.2	263.4	427.8	409.3	488.8	485.7							
Median	234.7	260.0	427.6	408.9	487.8	484.6							
Min	229.9	256.1	425.6	406.9	485.2	482.1							
Range	8.3	7.4	2.2	2.5	3.6	3.6							
Std Dev	0.2	0.3	0.1	0.3	0.1	0.1							



	rms AC Magnetic Field Measurement Statistics															
	Fund 60Hz (mG) 2nd (mG) 3rd (mG) 4th (mG) 5th (mG) 6th (mG) 7th (mG) Total AC (mG)													C (mG)		
	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor	Sensor
	1	2	1	2	1	2	1	2	1	2	1	2	1	2	1	2
Max	0.156	0.361	0.058	0.058	0.055	0.059	0.056	0.059	0.065	0.070	0.068	0.068	0.071	0.065	0.158	0.363
Median	0.067	0.148	0.009	0.009	0.010	0.011	0.010	0.010	0.013	0.022	0.010	0.010	0.011	0.014	0.073	0.152
Min	0.032	0.065	0.001	0.002	0.002	0.003	0.002	0.002	0.002	0.009	0.001	0.002	0.002	0.003	0.041	0.073
Range	0.124	0.297	0.057	0.056	0.053	0.056	0.054	0.057	0.063	0.061	0.067	0.066	0.070	0.062	0.117	0.290
Std Dev	0.006	0.013	0.003	0.003	0.003	0.004	0.003	0.003	0.004	0.005	0.004	0.004	0.004	0.004	0.006	0.013

Figure 14(d) Location 10: AC and DC Magnetic Field Measurement Results

April 2020









Figure 14(e) Location 10: Measured Environmental RF Levels


Non-Directional Data from Vertically Oriented Monopole Antenna, Bands 0-4











	Maximum Levels													
	Vertical Horizontal													
	Freq.		@		@		0		@					
Band	Range	Pk Min-Hold	Freq.	Pk Max-Hold	Freq.	Pk Min-Hold	Freq.	Pk Max-Hold	Freq.					
number	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)					
B5	B5 25~200 77.3 106.818 80.1 106.818 82.4 106.818 83.9 106.818													


JANUARY 2019


Figure 14(f) Location 10: Measured Environmental RF Levels


Band 5 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation











	Maximum Levels													
Vertical Horizontal														
	Freq.		0		@		8							
	Range	Pk Min-Hold	Freq.	Pk Max-Hold	Freq.	Pk Min-Hold	Freq.	Pk Max-Hold	@ Freq.					
Band	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)					
B6	200 ~ 2200	73.6	854.545	80.4	450.909	75.4	556.364	80.2	1752.727					


Figure 14(g) Location 10: Measured Environmental RF Levels

Band 6 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation

California High-Speed Rail Authority

April 2020





	Maximum Levels													
	Freq. Vertical Horizontal													
	Range	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.	Pk Min-Hold	@ Freq.	Pk Max-Hold	@ Freq.					
Band	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)	(dBuV/m/MHz)	(MHz)					
B7	B7 2000~6000 66.1 2727.273 69.8 2690.909 66.3 2647.273 68.5 2698.182													

Figure 14(h) Location 10: Measured Environmental RF Levels

Band 7 Vertical and Horizontal Components, Facing Alignment (0-deg) and at Peak Orientation